

RODENHOUSE



Fastening Systems

Thermal-Grip FastCap™

Faster. Stronger. Better.

APPROVED FOR USE WITH

DUPONT

Tyvek®

Thermal-Grip FastCap™

Mechanical attachment of Dupont™ Tyvek® CommercialWrap and CommercialWrap D. Available in hilo or sds (self-drilling screws) for wood or steel substrates in lengths ranging from 1 5/8" - 6".

Air-Barrier Performance

2" diameter solid cap washer helps seal the air barrier penetration. Attaches wrap over gypsum, plywood/osb or rigid foam insulation.

Labor-Saving Tools Available

Optional labor-saving 2" diameter cup adaptor fits commonly available autofeed screw guns. (Available as complete system from Rodenhouse Inc.)

Pre-assembled



1000 pcs. pre-assembled

SDS (12-18 gauge steel studs) - 1 5/8", 2", 2 1/2", 3", 3 1/2", 4", 4 1/2", 5 1/2", or 6"
HiLo (wood or 20-25 gauge steel studs) - 1 5/8", 2", 2 1/2", 3", 3 1/2", 4", 5", or 6"



-or-

Autofeed system



1000 pcs. each washers w/ collated screws

SDS (12-18 gauge steel studs) - 1 5/8", 2", 2 1/2", or 3"
HiLo (wood or 20-25 gauge steel studs) - 1 5/8", 2", 2 1/2", or 3"



MADE IN USA

Dupont™ Tyvek® is a registered trademark



*Patented and/or patent pending

www.ThermalGripFastCap.com

616-454-3100